TAIYO AMERICA, INC.

2675 Antler Drive, Carson City, NV 89701 Phone: (775) 885-9959 Fax: (775) 885-9972

CERTIFICATE OF ANALYSIS and CONFORMANCE

This is to certify that the following product has been inspected prior to sale and shipment, and complies with Taiyo America's manufacturing specifications for this product.

This product meets all the requirements of IPC-SM-840E Classes H and T and Bellcore (Telecordia) GR-78-CORE and is UL recognized 94V-0 (File #E166421, UL Name: PSR-9000AC).

Lot# 0042017

Mfg. Date: H - 20 - 20 Warranty Ends: | - 20 - 21

MANUFACTURING PROPERTY TEST METHOD SPECIFICATION RESULT VISCOSITY Toki Sangyo RE100U Viscometer Before mixing: 180 - 220 ps 5 rpms @ 25°C After mixing: 140 - 180 ps ps FINENESS OF GRIND TAI-0-0002 microns 15 microns maximum VISUAL EXAMINATION Microscopic examination: **Passed** 1. 1-mil drawdown of wet film 1 No bubbles, pits, voids, particles, color differences. 2. Wet film drawdown on No bubbles, pits, voids, Passed grind gauge particles, color differences. **RESISTANCE TO** 260°C (500°F) / 10 sec x 1 cycle Passed No discoloration, peeling, **SOLDERING** (*) Rosin-based flux or blistering FLEXIBILITY (*) **Passed** TAI-0-0025 No cracking

100/100 on copper

(*) - Final cure for these tests was 60 minutes @ 150°C (302°F) in a convection oven

TAI-0-0021

Verified By:

A.C. SUPERVISOR 4/22/20

Name, Title, Date

Passed

ADHESION (*)

PSR-9000 FXT GREEN