## TAIYO AMERICA, INC.

2675 Antler Drive, Carson City, NV 89701 Phone: (775) 885-9959 Fax: (775) 885-9972

## CERTIFICATE OF ANALYSIS and CONFORMANCE

This is to certify that the following product has been inspected prior to sale and shipment, and complies with Taiyo America's manufacturing specifications for this product.

This product meets all the requirements of IPC-SM-840E Classes H and T and Bellcore (Telecordia) GR-78-CORE and is UL recognized 94V-0 (File #E166421, UL Name: S-222NA).

78-CORE and is UL recognized 94 v-0 (File #E100421, UL Name: S-222NA).					
S-222NA (402-LV)	Lot# 9111927	Mfg. Date: \land 1 - \land - \land Warranty Ends: S - \land 9	9 - 20		
		MANUFACTURING			
<b>PROPERTY</b>	TEST METHOD	<b>SPECIFICATION</b>	RESU	<u>LT</u>	
VISCOSITY	Toki Sangyo RE100U Viscometer	Before mixing: Report Only	3,800	cps	
	5 rpms @ 25°C	After mixing: Report Only	0,500	cps	
	Brookfield DV-II Viscometer		-		
	10 rpms @ RT, spindle #6, 5 mins.	After mixing: 47,000 - 57,000 cps	52,8	800 cps	
THIXOTROPIC INDEX	Toki Sangyo RE100U Viscometer		2.0	•	
	Viscosity ratio: 5 rpm / 50 rpm	After mixing: Report Only	<i>3</i> .0		
FINENESS OF GRIND	TAI-0-0002	15 microns maximum	5	microns	
VISUAL EXAMINATION	Microscopic examination:				
4.7	1. 1-mil drawdown of wet film	No bubbles, pits, voids, particles, color differences.	Passed		
	2. Wet film drawdown on grind gauge	No bubbles, pits, voids, particles, color differences.	Passed	<b>V</b>	
SCREENABILITY	Visual inspection of coated panel	No surface defects, such as bubbles, pinholes, etc.	Passed		
RESISTANCE TO	260°C (500°F) / 10 sec x 3 cycles	No discolantian making	Passed		
SOLDERING (*)	Rosin-based flux	No discoloration, peeling,	1 asseu		
SOLDERING ( )	Rosin-Dased Hux	or blistering	*	<b>3</b>	
SOLVENT	Immersion in PM Acetate	No swelling, softening,	Passed		
RESISTANCE (*)	20°C / 30 mins.	or blistering			
PENCIL HARDNESS (*)	TAI-0-0020	6H or greater	8 H		
ADHESION (*)	TAI-0-0021	100/100 on copper	Passed	<u>u</u>	
(*) - Final cure for these tests was 20 minutes @ 140°C (284°F) in a convection oven					
WARRANTY EXTENSION					
		37 'M 1 T34			

This product retested by the America Qua Control departed and has been a warranty ex	ne Taiyo ility rtment n granted			
Warranty period ends:				
06/19/20	)			
Authorized By:				
Luis Marquez				

QC Supervisor

FRM-0-0042

Verified By:

The form of the service of the servic

10/14/11