TAIYO AMERICA, INC.

2675 Antler Drive, Carson City, NV 89701 Phone: (775) 885-9959 Fax: (775) 885-9972

CERTIFICATE OF CONFORMANCE

This is to certify that the following product has been inspected prior to sale and shipment, and complies with the manufacturing specifications for this product.

This product meets the performance requirements of A-A-56032D, Type II, as it applies to printed circuit board applications and the requirements of Bellcore GR-78-CORE Issue 1, September 1997 for legend and Marking Inks.

S-200E (LV)	Lot# 9120357	Mfg. Date: 12-03 Warranty Ends: 6-6	-19
PROPERTY VISCOSITY	TEST METHOD Toki Sangyo RE100U Viscome 5 rpms @ 25°C	MANUFACTURING SPECIFICATION Before mixing: Report Only After mixing: 210 – 250	RESULT /26 ps 222 ps
THIXOTROPIC IN	Toki Sangyo RE100U Viscom Viscosity ratio: 5 rpm / 50 rpm		1.4
FINENESS OF GRI	IND TAI-0-0002	17.5 microns maximum	5 microns
VISUAL EXAMINA	ATION Microscopic examination: 1. 1-mil drawdown of wet film	m No bubbles, pits, voids, particles, color differences.	Passed
	2. Wet film drawdown on grind gauge	No bubbles, pits, voids, particles, color differences.	Passed 💟
SCREENABILITY	Visual inspection of coated pa	anel No surface defects, such as bubbles, pinholes, etc.	Passed
RESISTANCE TO SOLDERING (*)	260°C (500°F) / 10 sec x 2 cyc Rosin-based flux	cles No discoloration, peeling, or blistering	Passed
SOLVENT RESISTANCE (*) PENCIL HARDNE	Immersion in PM Acetate 20°C / 30 mins. ESS (*) TAI-0-0020	No swelling, softening, or blistering 6H or greater	Passed
ADHESION (*)	TAI-0-0021	100/100 on copper	Passed
(*) - Final Th ret An Co an	tested by the Taivo	Verified By: Q.C. Supervision	* ************************************

Authorized By:
Luis Marquez
QC Supervisor

FRM-0-0075

a warranty extension.

Warranty period ends:

07/03/20

12/02/13

Date

Title,