TAIYO AMERICA, INC.

2675 Antler Drive, Carson City, NV 89701 Phone: (775) 885-9959 Fax: (775) 885-9972

CERTIFICATE OF CONFORMANCE

This is to certify that the following product has been inspected prior to sale and shipment, and complies with Taiyo America's manufacturing specifications for this product. This product meets the requirements of IPC-SM-840E Classes FH and FT.

| PSR-9000 LDI Amber | Lot# 9111947 | Mfg. Date: 11-19-19 Warranty Ends: 5-19 | 7-20 |
|-----------------------------|--|---|----------------------|
| PROPERTY VISCOSITY | TEST METHOD Toki Sangyo RE100U Viscometer 5 rpms @ 25°C | MANUFACTURING SPECIFICATION Before mixing: Report Only After mixing: 140 - 200 ps | RESULT 2/8 ps /63 ps |
| THIXOTROPIC INDEX | Toki Sangyo RE100U Viscometer Viscosity ratio: 5 rpm / 50 rpm | After mixing: Report Only | 1-2 |
| FINENESS OF GRIND | TAI-0-0002 | 5 Microns maximum | 5 microns |
| RESISTANCE TO SOLDERING (*) | 260°C (500°F) / 10 sec x 1 cycle Rosin-based flux | No discoloration, peeling, or blistering | Passed 🗸 |
| FLEXIBILITY (*) | TA1-0-0025 | No cracking | Passed 🗹 |
| ADHESION (*) | TAI-0-0021 | 100/100 on copper | Passed 🗹 |

(*) - Final cure for these tests was 60 minutes @ 150°C (302°F) in a convection oven

WARRANTY EXTENSION

This product has been retested by the Taiyo America Quality Control department and has been granted a warranty extension.

Warranty period ends:

06/19/20

Authorized By:

Luis Marquez

QC Supervisor

Verified By:

Titl

Date

FRM-0-0180

07/10/17