TAIYO AMERICA, INC.

2675 Antler Drive, Carson City, NV 89701 Phone: (775) 885-9959 Fax: (775) 885-9972

CERTIFICATE OF ANALYSIS and CONFORMANCE

This is to certify that the following product has been inspected prior to sale and shipment, and complies with Taiyo America's manufacturing specifications for this product.

This product meets all the requirements of IPC-SM-840E Classes H and T and Bellcore (Telecordia) GR-78-CORE and is UL recognized 94V-0 (file #E166421, UL Name: PSR-4000JA).

PSR-4000 LDI (US) Black

Luis Marquez

QC Supervisor

Lot # 0102927

Mfg. Date: し0 - 29 - 20 Warranty Ends: 4 - 29 - 21

01/04/12

| | | • | | warranty En | us: (- /- | | |
|--|----------------|--|----------------|--|---------------------|---------------------------|-----------------|
| PROPERTY VISCOSITY | | TEST METHOD Toki Sangyo RE100U Viscomet 5 rpms @ 25°C | er Be | ANUFACTUR PECIFICATION Of the state of the s | ON Only | <u>RESI</u> 442 263 | JLT ps ps |
| THIXOTROPIC INDEX | | Toki Sangyo RE100U Viscomet Viscosity ratio: 5 rpm / 50 rpm | | ter mixing: Report O | | 1.4 | |
| FINENESS OF GRIND | | TAI-0-0002 | 5 1 | 5 microns maximum | | 5 | microns |
| VISUAL EXAMINATION | | Microscopic examination: | | | | | |
| 4. ¹ | | 1. 1-mil drawdown of wet film | | bubbles, pits, voids, rticles, color differenc | | Passed | Ø |
| | | 2. Wet film drawdown on grind gauge | | bubbles, pits, voids, rticles, color differenc | ees. | Passed | 9 |
| SCREENABILITY | | Visual inspection of screen printed panel | | No surface defects, such as bubbles, pinholes, etc. | | Passed | |
| TACK-DRY | | Hot air convection oven 80°C / 30 minutes | Ta | Tack-free to the touch | | Passed | I |
| IMAGING | | ORC HMW 680GW - 7 kW 100 mJ / cm ² | | Stouffer 21 step: 12 - 16 (clear on copper) | | 13 | |
| | | Horizontal Developer - 1% Na20 30°C (86°F) / 60 secs., 28 psi | | , | , | ; | |
| RESISTANCE TO SOLDERING (*) | • | 260°C (500°F) / 30 sec x 1 cycle Rosin-based flux | | discoloration, peeling | , | Passed | V: |
| SOLVENT | | Immersion in PM Acetate | | No swelling, softening, | | Passed | [d |
| RESISTANCE (*) | | 20°C / 20 mins. | or l | or blistering | | | ٧ |
| PENCIL HARDNESS (*) | | TAI-0-0020 | 6 Ĥ | 6H or greater | | 8 H | |
| (*) - Final cure (*) - Final cure Contro and ha a warra Warrant | | nnty extension roduct has been ed by the Taiyo ca Quality 50 C (b) department as been granted anty extension. ty period ends: | | 100/100 on copper | | Passed | 14 |
| | | | | (302°F) in a convection oven | | | |
| | | | | Verified By: | | | 6/20 |
| | | 05/29/21 | N ₂ | ime. | Title | <u> </u> | ote |
| FRM-0-0202 | Authorized By: | | 210 | | - 1010 ₉ | D | a i C |
| | Luic Ma | PALIST | | | | , | 11/04/19 |