TAIYO AMERICA, INC.

2675 Antler Drive, Carson City, NV 89701 Phone: (775) 885-9959 Fax: (775) 885-9972

CERTIFICATE OF ANALYSIS and CONFORMANCE

This is to certify that the following product has been inspected prior to sale and shipment, and complies with Taiyo America's manufacturing specifications for this product.

PSR-4000 CR01MW	Lot#0120417	Mfg. Date: 12-04- Warranty Ends: 6-0 4	20
PROPERTY VISCOSITY	TEST METHOD Toki Sangyo RE100U Viscometer 5 rpms @ 25°C	MANUFACTURING SPECIFICATION After mixing: 150 - 200 ps	RESULT
THIXOTROPIC INDEX		After mixing: 1.00 - 2.50	1.27
FINENESS OF GRIND	TAI-0-0002	15 Microns or less.	5 microns
VISUAL EXAMINATIO	N Microscopic examination:		
	1. 1-mil drawdown of wet film	No bubbles, pits, voids, particles, color differences.	Passed 😈
	2. Wet film drawdown on grind gauge	No bubbles, pits, voids, particles, color differences.	Passed U
SCREENABILITY	Visual inspection of screen printed panel	No surface defects, such as bubbles, pinholes, etc.	Passed 🗹
TACK-DRY	Hot air convection oven	Tack-free to the touch	Passed 🗹
IMAGING	ORC HMW 680GW - 7 kW	Stouffer 21 step: Report Only (clear on copper)	10
· ·	Horizontal Developer - 1% Na2CO3 30°C (86°F) / 60 secs., 28 -32 psi.		
RESISTANCE TO SOLDERING (*)	260°C (500°F) / 10 sec x 3 cycles Rosin-based flux	No discoloration, peeling, or blistering	Passed 🔽
SOLVENT RESISTANCE (*)	Immersion in PM Acetate 20°C / 30 mins.	No swelling, softening, or blistering	Passed U
PENCIL HARDNESS (*) TAI-0-0020	4H or greater	6 H .
ADHESION (*)	TAI-0-0021	100/100 on copper	Passed 📝
(*) - Final cure for these tasts was 60 minutes @ 150°C (302°F) in a convection oven			
WARRANTY EXTENSION			
retest Ameri Contro and h	product has been ed by the Taiyo ca Quality of department as been granted ranty extension.	Verified By: A.C. Sulervi Name, Title,	
Warrar	ty period ends: 07/04/21		09/25/19

Authorized By: Luis Marquez QC Supervisor